

Specification Data Sheet

20oz IMO fabric-backed vinyl wallcovering



Physical Properties

Total Weight (Avg.)	452g/m ² (20oz / LY)
Width (approx.)	132 / 137cm
Roll Length (approx.)	27.4m
Fabric Backing	Polyester Cotton - Osnaburg

Fire Safety

IMO-compliant to order
Class "0" & "1" to BS476, parts 6 & 7
Euro Class B-s2, d0 to BS EN 13501-1
Class A to ASTM E-84 Tunnel Test

Bespoke Services

Custom colours & designs are available

Environment and Health

- Highly cleanable. Withstands hospital-grade cleaners & disinfectants when used as directed
- PFOA free – does not contain Perfluorooctanoic Acid
- Cadmium and Mercury free
- Non-Phthalate - Does not contain DEHP Plasticisers
- Low VOC
- Free of PBDE's (Polybrominated Diphenyl Ethers)
- Antimicrobial additives built in

Installation

Reverse hang / Random match

NB. Some items may have a pattern repeat or special hanging instructions. Please check with Seltex if unsure.

Adhesives & Primers

For IMO-compliance use Roman Pro 732. Available from your nearest stockist.
For other installations Seltex Primer Sealer, Seltex Heavy Adhesive and Seltex Sealed Surface Adhesive (VOV) are recommended and should be used as appropriate.

Warranty

Seltex fabric-backed vinyl wallcoverings are guaranteed to be free of defects in workmanship and material for five years.

© All Seltex designs are copyrighted

Seltex Interiors Ltd. 1 Horizon Trade Park, Ring Way, London N11 2NW, UK

Tel: +44 (0)20 8211 3107 Email: sales@seltex.co.uk

www.seltex.co.uk