

## Specification Data Sheet

### 24oz fabric-backed vinyl wallcovering



#### Physical Properties

Total Weight (Avg.)	542 g/m <sup>2</sup> (24oz / LY)
Width (approx.)	132 / 137cm
Roll Length (approx.)	27.4m
Fabric Backing	Polyester Cotton - Osnaburg

#### Fire Safety

Class "0" & "1" to BS476, parts 6 & 7  
Euro Class B-s2, d0 to BS EN 13501-1  
Class A to ASTM E-84 Tunnel Test

#### Bespoke Services

Custom colours, designs, weights, and micro-venting are available

#### Environment and Health

- Highly cleanable. Withstands hospital-grade cleaners & disinfectants when used as directed
- PFOA free – does not contain Perfluorooctanoic Acid
- Cadmium and Mercury free
- Non-Phthalate - Does not contain DEHP Plasticisers
- Low VOC
- Free of PBDE's (Polybrominated Diphenyl Ethers)
- Antimicrobial additives built in

#### Installation

Reverse hang / Random match

NB. Some items may have a pattern repeat or special hanging instructions. Please check with Seltex if unsure.

#### Adhesives & Primers

Seltex Primer Sealer and Seltex Heavy Adhesive are recommended.  
Seltex Sealed Surface Adhesive (VOV) is also available.

#### Warranty

Seltex fabric-backed vinyl wallcoverings are guaranteed to be free of defects in workmanship and material for five years.

© All Seltex designs are copyrighted