

## Seltex Paperback Specification Data Sheet



### Performance Specifications

Total Weight (Avg.)	160 to 380g/m <sup>2</sup> depending on design
Width (approx.)	53cm
Roll Length (approx.)	10m
Fabric Backing	Non-Woven

### Fire Rating

B-s2-d0 to BS EN 13501-1: 2007  
Class "0" & "1" to BS476, parts 6 & 7  
Class A to ASTM E-84

### Bespoke Services

Custom colours, designs, weights, widths and micro-venting are available

### Environmental and Health

- Recyclable
- Dynamic manufacturing materials recovery and reuse programme
- Highly cleanable water-based inks
- PFOA free – does not contain Perfluoro Octonic Acid
- Cadmium and Mercury free
- Free of PBDE's (Brominated Flame Retardants)
- Does not contain DEHP Plasticisers
- Antimicrobial additives built in

### Installation

Straight Hang / Random match

NB. Some items may have a pattern repeat or special hanging instructions. Please check with Seltex if unsure.

### Adhesive & Primers

Seltex Primer Sealer and Seltex Heavy Adhesive are recommended.  
Seltex Sealed Surface Adhesive (VOV) is also available.

### Warranty

Seltex fabric-backed vinyl wallcoverings are guaranteed to be free of defects in workmanship and material for five years.

**Seltex Interiors Ltd. 1 Horizon Trade Park, Ring Way, London N11 2NW, UK**

**Tel: +44 (0)20 8211 3107 Fax: +44(0)20 8368 0838 Email: sales@seltex.co.uk**

**www.seltex.co.uk**