



SELTEX PRIMER ACP

WALLCOVERING

Technical Data Sheet

Revised: 01/10/2018

DESCRIPTION

Universal acrylic primer suitable for surface preparation of walls and floors.

- Top efficacy
- High yield
- Low V.O.C. content
- Contains antibacterial and anti-mould additives

Suitable for:

- Surface preparation of walls and floors

SURFACE PREPARATION

Surfaces should be sound, dry, clean and free from damp, dust and grease. Any cracks or holes should be filled and high spots sanded level. Any existing mould should be dealt with and steps taken to prevent future reappearance.

PREPARATION OF THE PRODUCT

Seltex Primer ACP has to be diluted with clean water, recommended dilution ratio 1:4/5
(1L of Seltex Primer Sealer + 4/5L of clean water)

APPLICATION

ROLLER/BRUSH - After dilution the primer can be immediately applied to the surface.
The product is usually completely dry in 2/3 hours.

CONSUMPTION

Approximately 200 m² per 5 kg tub

CLEANING

We recommend to clean all work tools with water, immediately after the application.

CONTRAINDICATIONS

Seltex Primer ACP is not suitable on non-absorbent surfaces (ceramic, glass, etc.)

PACKAGES

1Kg Plastic bottle
5Kg Plastic tank

STORAGE

The product is guaranteed for 24 months from the date of production. Prevent from freezing (keep temperature between 5°C to 40°C)

TECHNICAL DATA

Base:	acrylic
Physical appearance:	liquid
Colour:	white
pH:	7.5
Viscosity:	2000-3000 cps
V.O.C.:	<0.05 g/m ³
Percentage of solid:	about 30%
Customs code:	3506 9190
Application temperature:	between 5°C to 40°C
Drying time:	2-4 hours
Non-flammable	

FINAL PROVISIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials.

