

Specification Data Sheet

20oz Fabric-backed vinyl wallcovering now includes 20% pre-consumer recycled material



Performance Specifications

Construction	20% pre-consumer recycled content by weight
Total Weight (Avg.)	452g/m ² (20oz)
Width (approx.)	132 / 137cm (52/54")
Roll Length (approx.)	27.4m
Fabric Backing	Polyester Cotton Osnaburg

Fire Rating

B-s2-d0 to BS EN 13501-1: 2007
Class "0" & "1" to BS476, parts 6 & 7
Class A to ASTM E-84

Bespoke Services

Custom colours, designs, weights, widths and micro-venting are available

Environmental and Health

- Recyclable
- Dynamic manufacturing materials recovery and reuse programme
- Highly cleanable water-based inks
- PFOA free – does not contain Perfluoro Octonic Acid
- Cadmium and Mercury free
- Free of PBDE's (Brominated Flame Retardants)
- Does not contain DEHP Plasticisers
- Antimicrobial additives built in

LEED Support:

MR – Materials and Resources – Recycled Content
MR – Materials and Resources – Construction Waste Management
EQ – Indoor Environmental Quality – Low Emitting Materials

Installation

Reverse hang / Random match

NB. Some items may have a pattern repeat or special hanging instructions. Please check with Seltex if unsure.

Adhesives & Primers

Seltex Primer Sealer and Seltex Heavy Adhesive are recommended.
Seltex Sealed Surface Adhesive (VOV) is also available.

Warranty

Seltex fabric-backed vinyl wallcoverings are guaranteed to be free of defects in workmanship and material for five years.

© All Seltex designs are copyrighted