

24oz Fabric-backed vinyl wallcovering specification data sheet



Performance Specifications

| | |
|-----------------------|---------------------------|
| Total Weight (Avg.) | 542g/m ² |
| Width (approx.) | 132 / 137cm |
| Roll Length (approx.) | 27.4m |
| Fabric Backing | Polyester Cotton Osnaburg |

Fire Rating

B-s2-d0 to BS EN 13501-1: 2007
Class "0" & "1" to BS476, parts 6 & 7
Class A to ASTM E-84

Bespoke Services

Custom colours, designs, weights, widths and micro-venting are available

Environmental and Health

- Recyclable
- Dynamic manufacturing materials recovery and reuse programme
- Highly cleanable water-based inks
- PFOA free – does not contain Perfluoro Octonic Acid
- Cadmium and Mercury free
- Free of PBDE's (Brominated Flame Retardants)
- Does not contain DEHP Plasticisers
- Antimicrobial additives built in

Installation

Reverse hang / Random match

NB. Some items may have a pattern repeat or special hanging instructions. Please check with Seltex if unsure.

Adhesives & Primers

Seltex Primer Sealer and Seltex Heavy Adhesive are recommended.
Seltex Sealed Surface Adhesive (VOV) is also available.

Warranty

Seltex fabric-backed vinyl wallcoverings are guaranteed to be free of defects in workmanship and material for five years.

© All Seltex designs are copyrighted