

Seltex Upholstery Data sheet

Seltex Upholstery is hygienic and easily cleanable. Stains can be removed using standard detergents or alcohol properly diluted. It is also wear resistant, has antimicrobial and antibacterial additives included, is mildew resistant and treated to protect against U.V. rays, resulting in it excellent light resistance. These products are eco-friendly, free of heavy metals, formaldehyde, mercury and solvents.

Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to lighter colours. This phenomenon is increased by humidity and temperature and is irreversible. Seltex will not assume responsibility for dye transfer caused by external contaminants and possible permanent staining caused by this phenomenon.

Technical Details

- Weight: 650 +/- 10% gr/m2 UNI-EN-ISO 2286-2
- Total thickness: 1,00 +/- 10% mm UNI-EN-ISO 2286-3
- Composition: PVC and plasticisers 88%, polycotton 12%
- Breaking strength warp > = 300 N
- Breaking strength weft > = 200 N
- Elongation warp: > = 40%
- Elongation weft: > = 150%
- Dry tear resistance warp > = 150 N
- Dry Tear Resistance Weft > = 100 N
- Colour fastness: xenotest index > = 7Blue Scale
- Fire retardant: CL 1/IM; M2; CRIB 5; EN 1021 part 1 and 2; CA TB 117 LE – FAR 25.853 Appendix F to part 25, IMO
- Blood and body fluids penetration: Compliant ISO 16603:2004
- Martindale test = 51.200 cycles EN ISO 5470-2:2004
- Width: 138 cm
- Roll length: standard 30-35 Im



Fire retardant
IMO
CL 1/IM-M2
CRIB 5



Waterproof




Mildew resistant,
antibacterial and
antimicrobial



UV resistant Low
temp. resistant



Free of heavy
metals,
formaldehyde,
mercury and
solvents



Abrasion
resistant



Easy upholstery



Long life



Easy to clean



Soft touch



Chemical resistant
to acid, bases,
alcohol and
common solvent



High abrasion
resistance in-
depth metallic
colour

Please bear in mind colours displayed on your screen may not be accurate. Please request a sample.